

[Product Information]

Ver.1.2

IMX542-AAMJ

Diagonal 16.8 mm (Type 1.1) CMOS solid-state Image Sensor with Square Pixel for Monochrome Cameras

Description

The IMX542-AAMJ is a diagonal 16.8 mm (Type 1.1) CMOS active pixel type solid-state image sensor with a square pixel array and 16.19 M effective pixels. This chip features a global shutter with variable charge-integration time. This chip operates with analog 3.3 V, 2.9 V, digital 1.1 V, and interface 1.8 V quadruple power supply. High sensitivity and low dark current characteristics are achieved.

(Applications: FA cameras, ITS cameras)

Features

- ◆ CMOS active pixel type dots
- ◆ Built-in timing adjustment circuit, H/V driver and serial communication circuit
- ◆ Global shutter function
- ◆ Input frequency 37.125 MHz / 74.25 MHz / 54 MHz
- ◆ Number of recommended recording pixels: 5320 (H) × 3032 (V) approx. 16.13 M pixels
- ◆ Readout mode
 - All-pixel scan mode
 - Vertical / Horizontal 1/2 Subsampling mode
 - 2 × 2 FD binning mode
 - ROI mode
 - Vertical / Horizontal - Normal / Inverted readout mode
- ◆ Readout rate
 - Maximum frame rate in
 - All-pixel scan mode: 8 bit 52 frame/s, 10 bit 42 frame/s, 12 bit 36 frame/s
- ◆ Pulse Output Function
 - The monitor output for Exposure period
 - Programmable pulse output
- ◆ 8-bit / 10-bit / 12-bit A/D converter
- ◆ CDS / PGA function
 - 0 dB to 24 dB: Analog Gain (0.1 dB step)
 - 24.1 dB to 48 dB: Analog Gain: 24 dB + Digital Gain: 0.1 dB to 24 dB (0.1 dB step)
- ◆ I/O interface
 - SLVS (2 ch / 4 ch / 8 ch switching) output (594 / 297 / 891 / 445.5 Mbps per ch)
 - SLVS - EC (1 Lane / 2 Lane) output (4.752 / 2.376 / 1.188 Gbps per Lane)
- ◆ Recommended lens F number: 2.8 or more (Close side)

Pregius S

* Pregius S is a registered trademark or trademark of Sony Group Corporation or its affiliates. Pregius S is a global shutter sensor technology for active pixel-type CMOS image sensors. By stacking the signal processing on the back illuminated type CMOS Image Sensor it realizes small chip size and high sensitivity, whilst using the high picture quality global shutter pixel technology of Pregius.

Sony reserves the right to change products and specifications without prior notice.

"Sony", "SONY" logo are registered trademarks or trademarks of Sony Group Corporation or its affiliates.

Device Structure

◆ CMOS image sensor			
◆ Image size	Diagonal 16.8 mm (Type 1.1)	Approx. 16.19 M pixels	All-pixel
◆ Total number of pixels	5328 (H) × 3104 (V)	Approx. 16.53 M pixels	
◆ Number of effective pixels	5328 (H) × 3040 (V)	Approx. 16.19 M pixels	
◆ Number of active pixels	5328 (H) × 3040 (V)	Approx. 16.19 M pixels	
◆ Number of recommended recording pixels	5320 (H) × 3032 (V)	Approx. 16.13 M pixels	All-pixel
◆ Unit cell size	2.74 μm (H) × 2.74 μm (V)		
◆ Optical black	Horizontal (H) direction: Front 0 pixel, rear 0 pixel Vertical (V) direction: Front 64 pixels, rear 0 pixel		
◆ Package	230 pin LGA	21.0 mm (H) × 20.0 mm (V)	

Image Sensor Characteristics

(Tj = 60 °C)

Item		Value	Remarks
Sensitivity	Typ.	14510 Digit/lx/s	
Saturation signal	Min.	4094 Digit	

Basic Drive Mode

Drive mode	Recommended number of recording pixels	Maximum frame rate [frame/s]	Output interface	ADC [bit]
All pixel	5320 (H) × 3032 (V) approx. 16.13 M pixels	45	SLVS 8 ch	8
		52	SLVS – EC 2 Lane	
		36	SLVS 8 ch	10
		42	SLVS – EC 2 Lane	
		32	SLVS 8 ch	12
		36	SLVS – EC 2 Lane	
Vertical / Horizontal 1/2 subsampling	2660 (H) × 1516 (V) approx. 4.03 M pixels	150	SLVS 8 ch	8
		197	SLVS – EC 2 Lane	
		121	SLVS 8 ch	10
		160	SLVS – EC 2 Lane	
		119	SLVS 8 ch	12
		135	SLVS – EC 2 Lane	
2 × 2 FD binning mode	2660 (H) × 1516 (V) approx. 4.03 M pixels	150	SLVS 8 ch	8
		197	SLVS – EC 2 Lane	
		121	SLVS 8 ch	10
		160	SLVS – EC 2 Lane	
		119	SLVS 8 ch	12
		135	SLVS – EC 2 Lane	

[Product Information]

Ver.1.2

IMX542-AAQJ

Diagonal 16.8 mm (Type 1.1) CMOS solid-state Image Sensor with Square Pixel for Color Cameras

Description

The IMX542-AAQJ is a diagonal 16.8 mm (Type 1.1) CMOS active pixel type solid-state image sensor with a square pixel array and 16.19 M effective pixels. This chip features a global shutter with variable charge-integration time. This chip operates with analog 3.3 V, 2.9 V, digital 1.1 V, and interface 1.8 V quadruple power supply. High sensitivity and low dark current characteristics are achieved.

(Applications: FA cameras, ITS cameras)

Features

- ◆ CMOS active pixel type dots
- ◆ Built-in timing adjustment circuit, H/V driver and serial communication circuit
- ◆ Global shutter function
- ◆ Input frequency 37.125 MHz / 74.25 MHz / 54 MHz
- ◆ Number of recommended recording pixels: 5320 (H) × 3032 (V) approx. 16.13 M pixels
- ◆ Readout mode
 - All-pixel scan mode
 - Vertical / Horizontal 1/2 Subsampling mode
 - ROI mode
 - Vertical / Horizontal - Normal / Inverted readout mode
- ◆ Readout rate
 - Maximum frame rate in
 - All-pixel scan mode: 8 bit 52 frame/s, 10 bit 42 frame/s, 12 bit 36 frame/s
- ◆ Pulse Output Function
 - The monitor output for Exposure period
 - Programmable pulse output
- ◆ 8-bit / 10-bit / 12-bit A/D converter
- ◆ CDS / PGA function
 - 0 dB to 24 dB: Analog Gain (0.1 dB step)
 - 24.1 dB to 48 dB: Analog Gain: 24 dB + Digital Gain: 0.1 dB to 24 dB (0.1 dB step)
- ◆ I/O interface
 - SLVS (2 ch / 4 ch / 8 ch switching) output (594 / 297 / 891 / 445.5 Mbps per ch)
 - SLVS - EC (1 Lane / 2 Lane) output (4.752 / 2.376 / 1.188 Gbps per Lane)
- ◆ Recommended lens F number: 2.8 or more (Close side)

Pregius S

* Pregius S is a registered trademark or trademark of Sony Group Corporation or its affiliates. Pregius S is a global shutter sensor technology for active pixel-type CMOS image sensors. By stacking the signal processing on the back illuminated type CMOS Image Sensor it realizes small chip size and high sensitivity, whilst using the high picture quality global shutter pixel technology of Pregius.

Sony reserves the right to change products and specifications without prior notice.

"Sony", "SONY" logo are registered trademarks or trademarks of Sony Group Corporation or its affiliates.

Device Structure

◆ CMOS image sensor			
◆ Image size	Diagonal 16.8 mm (Type 1.1)	Approx. 16.19 M pixels	All-pixel
◆ Total number of pixels	5328 (H) × 3104 (V)	Approx. 16.53 M pixels	
◆ Number of effective pixels	5328 (H) × 3040 (V)	Approx. 16.19 M pixels	
◆ Number of active pixels	5328 (H) × 3040 (V)	Approx. 16.19 M pixels	
◆ Number of recommended recording pixels	5320 (H) × 3032 (V)	Approx. 16.13 M pixels	All-pixel
◆ Unit cell size	2.74 μm (H) × 2.74 μm (V)		
◆ Optical black	Horizontal (H) direction: Front 0 pixel, rear 0 pixel Vertical (V) direction: Front 64 pixels, rear 0 pixel		
◆ Package	230 pin LGA	21.0 mm (H) × 20.0 mm (V)	

Image Sensor Characteristics

(Tj = 60 °C)

Item		Value	Remarks
Sensitivity	Typ.	8620 Digit/lx/s	
Saturation signal	Min.	4094 Digit	

Basic Drive Mode

Drive mode	Recommended number of recording pixels	Maximum frame rate [frame/s]	Output interface	ADC [bit]
All pixel	5320 (H) × 3032 (V) approx. 16.13 M pixels	45	SLVS 8 ch	8
		52	SLVS – EC 2 Lane	
		36	SLVS 8 ch	10
		42	SLVS – EC 2 Lane	
		32	SLVS 8 ch	12
		36	SLVS – EC 2 Lane	
Vertical / Horizontal 1/2 subsampling	2660 (H) × 1516 (V) approx. 4.03 M pixels	150	SLVS 8 ch	8
		158	SLVS – EC 2 Lane	
		121	SLVS 8 ch	10
		152	SLVS – EC 2 Lane	
		110	SLVS 8 ch	12
		110	SLVS – EC 2 Lane	