

## GigE UI-6140SE

The UI-6140SE is a highly compact GigE camera with Sony CCD sensor in 1.2 Megapixel resolution (1280x960 pixels). Besides the lockable RJ45 port for GigE, the UI-6140SE comes with a 6-pin Hirose connector for power and digital I/Os (opto-coupled, up to 30 V).



## Specification

### The characteristics at a glance

Interface	GigE
Lens Mount	C-Mount
Sensor Technology	CCD (Sony)
Model Description (color)	UI-6140SE-C
Model Description (mono)	UI-6140SE-M
Resolution (h x v)	1280 x 960
Resolution Depth	12bit (14bit ADC)
Resolution Category / Pixel Class	1.2 Megapixel
Sensor Size	1/3"
Shutter	Global
max. fps in Freerun Mode	28 fps
Exposure Time in Freerun Mode	46µs - 1188ms
Exposure Time in Trigger Mode	46µs - 1188ms
AOI Modes	---
Binning Modes	---
Subsampling Modes	---
I/O - Strobe	1
I/O - Trigger	1
I/O - RS-232	-
I/O - GPIO	-
I/O - I2C	-
HDR (High Dynamic Range)	-
Sensor Model (m/c)	ICX445ALA / ICX445AQA
Pixelpitch in µm	3.75
Optical Size	4.800 x 3.600 mm
Protection Classes	IP30
Dimensions H/W/L	34.00 mm, 44.00 mm, 43.50 mm
Mass	108.00 g
Power Supply	12 V