

Technical drawing of the SVS-VISTEK FXO camera module, showing multiple views and dimensions.

Views:

- bottom view
- right view
- front view
- left view
- back view
- top view

Dimensions:

- 1/4 - 20 UNC (5,0 mm)
- 8 x M4 - 6H (5 mm)
- 34 mm
- 4,3 mm
- 11,8 mm
- 1" - 32 UN 2A (8,5 mm)
- Ø 30 mm
- 42 mm
- 50 mm
- 0,5 sensor cover glass
- 1 cover glass
- 17,526 optical distance
- 17,856 optical backfocus incl. cover glass compensation
- 18,086 mechanical adjustment without compensation
- 39 mm
- 33,7 mm
- 25,4 mm
- 15,6 mm
- 4,2 mm
- 0 mm
- 49,8 mm
- 20,3 mm
- 20 mm
- 11 mm
- 11 mm
- 4,6 mm
- 0 mm

Hirose Connector Pinout:

Pin	Signal
1	V IN- (GND)
2	V IN+ (10 - 25V)
3	IN 4 RxD (RS232)
4	OUT 4 TxD (RS232)
5	IN 1 (0 - 24V)
6	IN 2 (0 - 24V)
7	OUT 1 (open drain)
8	OUT 2 (open drain)
9	IN 3+ (opto IN+)
10	IN 3- (opto IN-)
11	OUT 3 (open drain)
12	OUT 0 (open drain)

DETAIL A
MAßSTAB 2 : 1

Technical Drawing FXO_CX-12_2C.pdf

SVS-VISTEK

Maßstab / Scale: 1:1

Version: 1

Benennung / Title: Technical_Drawing_FXO_CX-12_2C.pdf

Gezeichnet/Drawn: S.Seiler

Datum/Date: 12.07.2022

Geprüft / Appv'd: ---


Projekt: ---

Material: ---

Gewicht / Weight: ---

Ersatz für / replacement for: ---

Blatt / Sheet: 1 / 1

 SVS-VISTEK		Oberflächenbehandlung / Finish:		Maßstab / Scale: 1:1		Version 1			
				Alle Geometrien / Maße ohne andere Angaben, haben eine Form- und Lagetoleranz von ±0,1mm Alle Angaben in mm / zulässige Oberflächenrauhtiefe Rz 6,3 All geometric tolerances without another Instructions are ±0,1mm All Dimensions in mm / Surface Rz 6,3					
	Name	Datum/Date				Benennung / Title: Technical_Drawing_FXO_CX-12_2C.pdf			
Gezeich./Drawn	S.Seiler	12.07.2022							
Geändert/Changed									
Geprüft / Appv'd			Projekt : ---						
1.0 Fertigteil beinhaltet:			Material:		Zeichnungsnr./ Dwg-Nr. - Artikelnr.:			A3	
1.1 Blankteil									
1.2									
1.3									
			Gewicht / Weight:		Ersatz für / replacement for : ---			Blatt / Sheet 1 / 1	