



CLASS	NOMINAL LENGTH						PERPENDICULARITY TOLERANCE	CLASS	NOMINAL LENGTH ON SHORTER SIDE			
	L ≤ 10	10 < L ≤ 30	30 < L ≤ 100	100 < L ≤ 300	300 < L ≤ 1000	1000 < L ≤ 3000			L ≤ 100	100 < L ≤ 300	300 < L ≤ 1000	1000 < L ≤ 3000
H	±0.02	±0.05	±0.1	±0.2	±0.3	±0.4	H	±0.2	±0.3	±0.4	±0.5	
K	±0.05	±0.1	±0.2	±0.4	±0.6	±0.8	K	±0.4	±0.6	±0.8	±1.0	

CLASS	LENGTH OF SHORTER SIDE OF ANGLE				ANGLE TOLERANCE
	L ≤ 10	10 < L ≤ 50	50 < L ≤ 120	120 < L ≤ 400	
f	±1°	±30'	±20'	±10'	ORIGINAL SHEET FORMAT SIZE: A4
m	±1°	(±0.5°)	(±0.333°)	(±0.166°)	

CLASS	STANDARD DIMENSION RANGE			
	L < 0.2	0.2 ≤ L ≤ 0.5	0.5 < L ≤ 3	3 < L ≤ 6
f	±0.1	±0.2	±0.5	±1.0
m	±0.1	±0.2	±0.5	±1.0

CLASS	STANDARD DIMENSION RANGE			
	L < 0.2	0.2 ≤ L ≤ 0.5	0.5 < L ≤ 3	3 < L ≤ 6
f	±0.1	±0.2	±0.5	±1.0
m	±0.1	±0.2	±0.5	±1.0

FINISH BLACK ANODIZING	UNIT:mm	MORITEX Vision Creating Value
SURFACE	MODEL NAME	
MATERIAL	MML3-SR65VI-18C	
CHAMFER	PART NAME	
TOLERANCE CLASS	OUTLINE DRAWING	
SCALE	DRAWING NO.	
	A24294A0100101A-001	SHEET
		1/1

MARK	A-001	2022.Feb.08	NEW		
DESIGNED	Kodaira	DRAWN	Kodaira	CHECKED	APPROVED
				茅野	山中
				'22.02.10	'22.02.11

MAGNIFICATION / 光学倍率 : 3x
EFFECTIVE Fno / 有効Fno : 9.4-22
*1) NO RETAINING POSITION / 保持不可範囲